Genuine Parts

We provide our customers with full range of genuine parts including oil mist filters, vacuum pump oil, and third party components. Almost all requirements of our customers could be satisfied and our technical team is ready to help for selection of correct parts. Meanwhile with our professional know–how, we help to analyze the operating cost of our customers.

Oil Mist Filter

Model: Φ55 × 147
Applies to: VSV–20
Model: Φ55 × 215
Applies to: VSV–22/28
Model: Φ72 × 243
Applies to: VSV–40/65/100
Model: Φ72 × 425
Applies to: VSV–160/200/300

Oil Mist Filter/Filter Element

VOT-8A/B	Φ53x92
VOT-30B	Φ79x100
VOT-65C	Φ118x166

A for KF16; B for KF25; C for KF40

Dust Filter/Filter Element

Model: G3/4" Φ65x69
Applies to: VSV–20
Model: G1–1/4" Φ98x70
Applies to: VSV–40/65/100
Model: G2" Φ150x222
Applies to: VSV–160/200/300

Gas Ballast Element

Model: Φ12 × 20
Applies to: VSV–20/40/65
Model: Φ19 × 28
Applies to: VSV–100
Model: Φ32 × 24
Applies to: VSV–160/200/300

Scanned with CamScanner

Oil Filter

Model：Φ78 × 85
Applies to：VSV–40/65/100
Model：Φ93 × 140
Applies to：VSV–160/200/300

Tube Joints

Φ22×M20 Aluminum alloy; Applies to VRD-4/6/8/8M
Φ18×M20 Aluminum alloy; Applies to VRD-4/6/8/8M
Φ15×M20 Aluminum alloy; Applies to VRD-4/6/8/8M
Φ12×M20 Aluminum alloy; Applies to VRD-4/6/8/8M
Φ8×M20 Aluminum alloy; Applies to VRD-4/6/8/8M

KF Model Air Inlet

KF16 stainless steel; Applies to VRD-4/6/8/8M
KF25 stainless steel;
Applies to VRD-4/6/8/8M/16/16M/24/24M/30/30M
KF40 stainless steel;
Applies toVRD-24/24M/30/30M/48/48M/65/65M

55 Permanent seat

M20 Aluminum alloy; Applies to VRD-4/6/8/8M

O-Ring

VPS116 ΦA:18 ΦB:5.3
Applies to VRD-4/6/8/8M
VPS125 ΦA:28 ΦB:5.3
Applies to VRD-4/6/8/8M/16/16M/24/24M/30/30M
VPS140 ΦA:42 ΦB:5.3
Applies to VRD-24/24M30/30M/48/48M/65/65M

Hoop

VPS216 A:45 B:61 C:16 ΦD:22
Applies to VRD-4/6/8/8M
VPS225 A:55 B:72 C:16 ΦD:32
Applies to VRD-4/6/8/8M/16/16M/24/24M/30/30M
VPS240 A:70 B:90 C:18 ΦD:47
Applies to VRD-24/24M/30/30M/48/48M/65/65M

Center Reset

VPS316 ΦA:17 ΦB:16 C:3.9 D:8
Applies to VRD-4/6/8/8M
VPS325 ΦA:26 ΦB:25 C:3.9 D:8
Applies to VRD-4/6/8/8M/16/16M/24/24M/30/30M
VPS340 ΦA:41 ΦB:40 C:3.9 D:8
Applies to VRD-24/24M/30/30M/48/48M/65/65M

Filter

VPS416 ΦA:17 ΦB:16 C:3.9 D:8 E:21
Applies to VRD-4/6/8/8M
VPS425 ΦA:26 ΦB:25 C:3.9 D:8 E:21
Applies to VRD-4/6/8/8M/16/16M/24/24M30/30M
VPS440 ΦA:41 ΦB:39 C:3.9 D:8 E:36
Applies to VRD-24/24M/30/30M/48/48M/65/65M
VPS425A
Applies to VRD-4/6/8/8M
VPS440A
Applies to VRD-24/24M/30/30M

Flange

VPS516 ΦA:30 ΦB:18.2 D:4.5
Applies to VRD–4/6/8/8M
VPS525 ΦA:40 ΦB:27.2 D:4.5
Applies to VRD–4/6/8/8M/16/16M/24/24M/30/30M
VPS540 ΦA:50 ΦB:42.2 D:5
Applies to VRD–24/24M/30/30M/48/48M/65/65M

Pump Oil

VPO-46H
Applies to：VSV-20；VRD-4/6/8/8M
VPO-68H
Applies to：VSV-20/22/28/40/65/100/
160/200/300
VRD-16/16M/24/24M/30/30M
VPO-100H
Applies to：VRD-48/48M/65/65M

Adapter

Customized according to customers' requirements

Scanned with CamScanner