- Automatic and compact vacuum plants fitting medical norms in force
- Lubricated rotary vane vacuum pumps EVISA MV type
- Shock mounts
- Electric motors PF55 type – F class (special motors on request)
- Available regulation modes (see the set-up layout)
- Fit to EN 737-3 standard
- Option FLEXO constant vacuum : regulation device allowing to use small capacity receivers
- Remote control through J-BUS connection (RS 485) with CYCLIC 2000 J or PROCOM control boards
- Integrated bacterial filtration
- Delivery pot for condensate recuperation
- Connection for additional receiver (in case of "ON/OFF CONTROL" regulation type)
- Integrated network alarm
- Included suction and exhaust hoses
- Ready-to-run plants

## Characteristics

| | NOMINAL CAPACITY $m^3.h^{-1}$ | | POWER kW | | NOISE LEVEL dB(A) | OIL FILLING L | RECEIVER CAPACITY L | FILTRATION | WEIGHT kg |
|---|---|---|---|---|---|---|---|---|---|
| | 50 Hz | 60 Hz | 50 Hz | 60 Hz | | | | | |
| HOSPIVAC 2 E17 | 2 x 17 | 2 x 20 | 2 x 0,55 | 2 x 0,66 | 59 | 2 x 1,5 | 300 | FD 30 B or D | 200 |
| HOSPIVAC 2 E25 | 2 x 30 | 2 x 36 | 2 x 0,75 | 2 x 0,90 | 60 | 2 x 1,5 | 300 | FD 65 B or D | 205 |
| HOSPIVAC 2 E40 | 2 x 47 | 2 x 56 | 2 x 1,10 | 2 x 1,30 | 62 | 2 x 1,5 | 300 | FD 65 B or D | 225 |
| HOSPIVAC 2 E65 | 2 x 65 | 2 x 78 | 2 x 1,50 | 2 x 1,80 | 65 | 2 x 4,0 | 500 | FD 130 B or D | 320 |
| HOSPIVAC 2 E100 | 2 x 96 | 2 x 115 | 2 x 2,20 | 2 x 2,64 | 67 | 2 x 4,0 | 500 | FD 320 B or D | 340 |
| HOSPIVAC 2 E150 | 2 x 150 | 2 x 180 | 2 x 3,00 | 2 x 3,60 | 70 | 2 x 7,0 | 800 | FD 320 B or D | 460 |
| HOSPIVAC 2 E200 | 2 x 190 | 2 x 228 | 2 x 4,00 | 2 x 4,80 | 71 | 2 x 7,0 | 800 | FD 320 B or D | 490 |
| HOSPIVAC 2 E300 | 2 x 288 | 2 x 345 | 2 x 5,50 | 2 x 6,60 | 73 | 2 x 7,0 | 800 | FD 600 B or D | 660 |

## Available set-up

| Selected regulation | |
|---|---|
| PROCOM | ■ |
| CYCLIC 2000 J | ■ |
| MILLENIUM | ■ |

■ available

CE 0398

Range complying with 93/42/CE directive

## Standard power supplies

- 3-phase, 400V/50Hz or 460V/60Hz + Neutral
- Other tensions on request

1 STATUS device

2 Vertical vacuum receiver

Specifications are subject to be changed without notice

# Automatic vacuum plants for medical applications

## Dimensions

HOSPIVAC 2 E 17 to E 200




HOSPIVAC 2 E 300







| HOSPIVAC 2 | A | B | C | D | E | F | G | ØJ network | ØK exhaust |
|---|---|---|---|---|---|---|---|---|---|
| E17 | 1740 | 890 | 1030 | 300 | 995 | 210 | 330 | 3/4" | 3/4" |
| E25 | 1740 | 890 | 1030 | 300 | 995 | 210 | 330 | 3/4" | 3/4" |
| E40 | 1740 | 890 | 1030 | 300 | 995 | 210 | 330 | 1" | 1" |
| E65 | 1940 | 995 | 1240 | 360 | 1200 | 270 | 345 | 1"1/4 | 1"1/4 |
| E100 | 1940 | 995 | 1240 | 360 | 1200 | 270 | 345 | 1"1/2 | 1"1/2 |
| E150 | 2330 | 1195 | 1410 | 400 | 1500 | 340 | 390 | 2" | 2" |
| E200 | 2330 | 1195 | 1410 | 400 | 1500 | 340 | 390 | 2" | 2" |
| E300 | 2610 | 1300 | 1400 | 470 | 1500 | 410 | 390 | 2" | 2" |

Dimensions expressed in mm

## Plant references

| ON/OFF control regulation | E17 R3 | E25 R3 | E40 R3 | E65 R5 | E100 R5 | E150 R8 | E200 R8 | E300 R8 |
|---|---|---|---|---|---|---|---|---|
| HOSPIVAC 2 E AFS* | 916682 | 919378 | 919384 | 916605 | 916606 | 916607 | 916608 | 916609 |
| HOSPIVAC 2 CJ Exx-AFS* | 916683 | 919379 | 919385 | 914341 | 914347 | 914353 | 914359 | 914365 |
| HOSPIVAC 2 MIL Exx-AFS* | 916684 | 919380 | 919386 | 916612 | 916613 | 916614 | 916615 | 916616 |
| HOSPIVAC 2 PM Exx-AFD* | 916686 | 919381 | 919387 | 916619 | 916620 | 916621 | 916622 | 916623 |
| HOSPIVAC 2 CJ Exx-AFD* | 916687 | 919382 | 919388 | 914344 | 914350 | 914356 | 914362 | 914368 |
| HOSPIVAC 2 MIL Exx-AFD* | 916688 | 919383 | 919389 | 916626 | 916627 | 916628 | 916629 | 916630 |

| FLEXO constant vacuum regulation device | E17 R3 | E25 R3 | E40 R3 | E65 R5 | E100 R5 | E150 R8 | E200 R8 | E300 R8 |
|---|---|---|---|---|---|---|---|---|
| HOSPIVAC 2 PM Exx-AFS* | 919115 | 919116 | 919117 | 919118 | 919119 | 919120 | 919121 | 919122 |
| HOSPIVAC 2 CJ Exx-AFS* | 919123 | 919124 | 919125 | 919126 | 919127 | 919128 | 919129 | 919130 |
| HOSPIVAC 2 MIL Exx-AFS* | 919131 | 919132 | 919133 | 919134 | 919135 | 919136 | 919137 | 919138 |
| HOSPIVAC 2 PM Exx-AFD* | 919139 | 919140 | 919141 | 919142 | 919143 | 919144 | 919145 | 919146 |
| HOSPIVAC 2 CJ Exx-AFD* | 919147 | 919148 | 919149 | 919150 | 919151 | 919152 | 919153 | 919154 |
| HOSPIVAC 2 MIL Exx-AFD* | 918973 | 918974 | 918975 | 918976 | 918977 | 918978 | 918979 | 918980 |

* : AFS - simple filtration with by-pass  AFD - duplex filtration

## Accessory and option references

| | E17 R3 | E25 R3 | E40 R3 | E65 R5 | E100 R5 | E150 R8 | E200 R8 | E300 R8 |
|---|---|---|---|---|---|---|---|---|
| **Oil level security** for one pump | 616564 x 2 | | | 619196 x 2 | | | | |
| **Temperature security** for one pump | 618547 x 2 | | | | | | | |
| **Transformer 400V / 230V assembly** | if no neutral current | | | | | | | 611099 |
| **FLEXO or ON/OFF external control** | only with CYCLIC 2000J | | | | | weekly clock | | 613996 |
| **Clock forced running** | only with CYCLIC 2000J | | | | | possible if FLEXO control | | 617608 |
| **Audio-warning system for MILLENIUM** | | | | | | | | 618295 |
| 1 **STATUS device** | with PROCOM : 618068 | | | | with CYCLIC 2000J : 613995 | | | |
| 2 **Additional vertical receiver** for ON/OFF CONTROL regulation | | | 500 litres 710486 | 1000 litres 710488 | | 2000 litres 710490 | 2 x 2000 litres 2 x 710490 | |





Specifications are subject to be changed without notice