◎ JSP型螺杆真空泵主要性能参数
Technical parameter for JSP vacuum pump

项目ITEMS \ 型号MODEL	单位 Units	JSP-150	JSP-300	JSP-450	JSP-600
抽气速率/Pumping rate	m^3/h	140	274	430	570
极限压力/Utmost Pressure	Pa	5	5	5	5
进气口尺寸/Size of inlet	mm	40	50	65	80
排气口尺寸/Size of inlet	mm	30	40	50	50
噪音/Noise	dB (A)	78	78	80	80
电机额定功率/Motor Power	kW	4/5.5	7.5/11	11	15/18.5
电机同步转速/Motor synchronous speed	r/min	3000	3000	3000	3000
用油量/Oil consumption	L	1.3	1.6	1.8	2
冷却水/Cooling water	L/min	2	4	8	10

★正常情况下改变技术规格参数，恕不另行通知
We won't notice the changes of our technical specifications under normal circumstances.

● 前级过滤器/Pre-filter

◎ 概述/Summarize

前级过滤器是根据市场需求设计、研发的过滤产品，主要配置在食品包装、医疗设备等带有水汽并影响工作质量的行业中。其优点有：
1. 去除真空环境中的液态水分
2. 去除真空环境中的细微颗粒
3. 稳定抽气流量

Pre-filter is a filtration products which was designed and developed based on market demand. It's main configuration includes food packaging, medical equipment and other industries with water vapor which affect the quality of works. Its advantages are:
1. Remove the liquid water in a vacuum environment;
2. Remove the fine particles in a vacuum environment;
3. Stable the suction flow rate.

◎ 注意事项/Matters needing attention

此前级过滤器安装在真空泵和客户所需真空环境中间位置，在使用的过程中需注意以下几点：
1. 严格按过滤器的铭牌接入进出管路
2. 根据过滤器的污水的量定时通过排污阀排除污水。建议每班结束后排污
3. 根据过滤器内进入粉尘的量定时清洗过滤器内的过滤金属丝网，建议每周清洗一次。

This Pre-filter is installed in the middle position of vacuum pumps or vacuum environments clients demand . We should pay attention to the following points in the use of the process:
1. Access in and out of the pipeline in strict accordance with the filter plate;
2. Drain sewage through the drain valve timely according to the amount of the filter bearing. Suggest drain the sewage after each class;
3. Regularly clean the filter wire mesh in the filter according to the amount of entering dust.
Recommend cleaning once a week.

◎ PF-27/42前级过滤器技术参数
PF-27/42Technical parameter for Pre-filter

型号MODEL	单位 Units	PF-27	PF-42
额定抽速/Rated Speed	m^3/h	≤100	≤302
额定压力/Utmost Pressure	mbar	0.05	0.05
泵的配置/Configuration	台	X-10~X-100	X-160~X-302
排气口螺纹/Whorl of outlet	inch	G11/4"	G2"
容积/Capacity	L	27	42
进气口螺纹/Whorl of inlet	inch	G11/4"	G2"
整机重量/Total weight	kg	19	39
外形尺寸/Vacuum pump size	cm	Φ220×1060	Φ275×1080

● 注：1.正常情况下改变技术规格参数，恕不另行通知。

2.根据客户的需求不同，过滤的介质有两种，一种为金属丝网，另一种为玻璃球。

1.We won't notice the changes of our technical specifications under normal circumstances.

2.According to the different needs of customers,we have two media for filter:one is golden screen,the other is glass spheres.